



Scan to explore
UXR10 online

Urban UXR10

10W IP65 Rated Recessed Trimless Downlight

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Accessories | Driver |
|--------------|--------------------|----------------------|-------------|--------------|------------------------|------------------------------|
| UXR10 | 2.7 (2700K) | (CRI 90+ Standard) | NB (Narrow) | W (White) | (Plaster Recessed Kit) | LT (Leading & Trailing Edge) |
| | 3 (3000K) | V (CRI 93+ VIVID) | MB (Medium) | DALI (DALI) | | |
| | 3.5 (3500K) | R (CRI 97+ Standard) | | 110V (1-10V) | | |
| | 4 (4000K) | | | | | |

Order Code **UXR104-MB-W-LT**



Product Features

- Engineered for an impeccable trimless finish, this fitting comes with a plaster recessed kit for a fully seamless look once installed
- Deep recessed LED downlight with IP65 rating, known for its thin trim profile and low glare design
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes




To configure this track light, please visit
trendlighting.com.au/product/urban-UXR10

Physical Characteristics

| | |
|-------------|------------------|
| Trim Colour | White |
| Dimensions | Ø82 x 120 (H) mm |
| Cutout | Circular 78 mm |
| Weight | 230 g |

Dimensions (mm)



Technical Characteristics

Based on UXR104-MB-W-LT

| | |
|--------------------|--|
| LED Power | 10W |
| LED Type | COB |
| Lumen Output | 1450 lm |
| Luminous Flux | 1025 lm |
| Efficacy | 87.61 lm/W |
| Colour Temperature | 2700K 3000K 3500K 4000K |
| Colour Technology | CRI 90+ CRI 93+ VIVID CRI 97+ |
| Colour Deviation | SDCM ≤ 3 |
| Lifetime | 50,000 hours (L80) |
| Beam Angle | Narrow Medium |
| System Power | 11.7W Typical |
| Driver Model | Trend 150218-300 (L&T) |
| Input | 180-265V AC 50/60 Hz |
| Output | 30-42V DC 300mA |
| Power Factor | >0.93 |
| Protection | OVP, OTP, OCP, SCP, OPP |
| Dimming | Leading & Trailing Edge DALI 1-10V |

General Characteristics

| | |
|--------------------|------------|
| Category | Downlights |
| Family | Urban |
| Surface | Ceiling |
| Mounting | Recessed |
| Insulation Contact | CA90 |
| Ingress Protection | IP65 |



Scan to explore
[UXR10](#) online

Urban UXR10


10W IP65 Rated Recessed Trimless Downlight

| Product Code | Colour Temperature | Colour Technology | Beam Angle | Trim Colour | Accessories | Driver |
|--------------|--------------------|----------------------|-------------|-------------|------------------------|------------------------------|
| UXR10 | 2.7 (2700K) | (CRI 90+ Standard) | NB (Narrow) | W (White) | (Plaster Recessed Kit) | LT (Leading & Trailing Edge) |
| | 3 (3000K) | V (CRI 93+ VIVID) | MB (Medium) | | | DALI (DALI) |
| | 3.5 (3500K) | R (CRI 97+ Standard) | | | | 110V (1-10V) |
| | 4 (4000K) | | | | | |

Order Code **UXR104-MB-W-LT**

To configure this track light, please visit
trendlighting.com.au/product/urban-UXR10

Accessories



Plaster Recessed Kit