



Scan to explore
UXT10 online

Urban UXT10

10W Recessed Adjustable Trimless Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories	Driver
UXT10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	(Plaster Recessed Kit)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)			DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)			110V (1-10V)
	4 (4000K)					

Order Code **UXT104-MB-W-LT**



Product Features

- Engineered for an impeccable trimless finish, this fitting comes with a plaster recessed kit for a fully seamless look once installed
- Recessed adjustable LED downlight, known for its thin trim and low glare design
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes




To configure this track light, please visit
trendlighting.com.au/product/urban-UXT10

Physical Characteristics

Trim Colour	White
Tilt Angle	20°
Dimensions	Ø82 x 105 (H) mm
Cutout	Circular 78 mm
Weight	215 g

Dimensions (mm)



Technical Characteristics

Based on UXT104-MB-W-LT

LED Power	10W
LED Type	COB
Lumen Output	1450 lm
Luminous Flux	1013 lm
Efficacy	86.58 lm/W
Colour Temperature	2700K 3000K 3500K 4000K
Colour Technology	CRI 90+ CRI 93+ VIVID CRI 97+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L80)
Beam Angle	Narrow Medium Wide
System Power	11.7W Typical
Driver Model	Trend 150218-300 (L&T)
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge DALI 1-10V

General Characteristics

Category	Downlights
Family	Urban
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP20



Scan to explore
[UXT10](#) online

Urban UXT10


10W Recessed Adjustable Trimless Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories	Driver
UXT10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	(Plaster Recessed Kit)	LT (Leading & Trailing Edge) DALI (DALI) 110V (1-10V)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)			
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)			
	4 (4000K)					

Order Code **UXT104-MB-W-LT**

To configure this track light, please visit
trendlighting.com.au/product/urban-UXT10

Accessories



Plaster Recessed Kit