

Midiled XMC225

2 x 25W Recessed Adjustable Rectangular Downlight



Scan to explore XMC225 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XMC225	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	ND (Non-dimmable) LT (Leading & Trailing Edge)
					DALI (DALI)

Order Code XMC2254-MB-W-ND




To configure this downlight, please visit trendlighting.com.au/product/midiled-XMC225

Physical Characteristics

Trim Colour	White Black			
Tilt Angle	35° x 35°			
Dimensions (LxWxH)	330 x 175 x 110 mm			
Spring Height	35 mm			
Cutout	Rectangular 310 x 160 mm			
Weight	1850 g			

Dimensions (mm)



Cutout 310 x 160 mm

Product Features

- Twin recessed adjustable LED downlight in rectangular housing
- Also available in a single spot (XMC125) or as a row of three (XMC325)
- CRI 90+ available in 3000K and 4000K CCT options
- Anodised black heatsink for effective thermal management ensuring high output and long lifespan
- Supplied with a remote driver

Product Attributes











Based on XMC2254-MB-W-ND			
2 x 25W			
COB			
5910 lm			
5000 lm			
94.70 lm/W			
3000K 4000K			
CRI 90+			
SDCM ≤ 3			
50,000 hours (L80)			
Medium			
52.8W Typical			
Trend 150020-700 (Non-dim) x 2			
180-265V AC 50/60 Hz			
30-40V DC 700mA			
>0.90			
OVP, OTP, OCP, SCP, OPP			
Non-dimmable			
Leading & Trailing Edge DALI			

General Characteristics

Category	Downlights
Family	Midiled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Midiled XMC225

Scan to explore XMC225 online

2 x 25W Recessed Adjustable Rectangular Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XMC225	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	MB (Medium)	W (White) B (Black)	ND (Non-dimmable) LT (Leading & Trailing Edge) DALI (DALI)

Order Code XMC2254-MB-W-ND

To configure this downlight, please visit

trendlighting.com.au/product/midiled-XMC225

Trim Colour





White Trim

Black Trim