

Miniled XDV10

10W IP65 Rated Recessed Downlight



Scan to explore XDV10 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XDV10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)		110V (1-10V)
	4 (4000K)				

Order Code XDV104-WB-W-LT




To configure this downlight, please visit trendlighting.com.au/product/miniled-XDV10

Physical Characteristics

Trim Colour	White Black		
Dimensions	Ø140 x 140 (H) mm		
Spring Height	20 mm		
Cutout	Circular 125 mm		
Weight	450 g		

Dimensions (mm)



Product Features

- Recessed low glare LED downlight with IP65 rating
- Manufactured with an aluminium body and powder coat finish
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver

Product Attributes













Technical Characteristics	Based on XDV104-WB-W-L			
LED Power	10W			
LED Type	COB			
Lumen Output	1450 lm			
Luminous Flux	1028 lm			
Efficacy	87.86 lm/W			
Colour Temperature	2700K 3000K 3500K 4000K			
Colour Technology	CRI 90+ CRI 93+ VIVID CRI 97+			
Colour Deviation	SDCM ≤ 2			
Lifetime	50,000 hours (L80)			
Beam Angle	Narrow Medium Wide			
System Power	11.7W Typical			
Driver Model	Trend 150218-300 (L&T)			
Input	180-265V AC 50/60 Hz			
Output	30-42V DC 300mA			
Power Factor	>0.93			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Leading & Trailing Edge DALI 1-10V			

General Characteristics

Category	Downlights
Family	Miniled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP65



Miniled XDV10



10W IP65 Rated Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
XDV10	2.7 (2700K)	(CRI 90+ Standard)	NB (Narrow)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	MB (Medium)	B (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)	WB (Wide)		110V (1-10V)
	4 (4000K)				

Order Code XDV104-WB-W-LT

To configure this downlight, please visit

trendlighting.com.au/product/miniled-XDV10

Trim Colour





White Trim

Black Trim