

## Mono ZSB20

16 Watt 600mm Tri-colour Diffused Batten

Surface mounted diffused SMD LED batten featuring screwless design and manufactured with an aluminium powder coated body with high transmittance polycarbonate diffuser for wide light coverage. An ideal lighting solution for general lighting applications.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white) and 5700K (daylight). Supplied with an integral flicker free driver and terminal block.

Product	CCT	Trim Colour	Driver	Order Code
ZSB20	Tri-colour	White Trim	Non-dim	ZSB20-TRI-W-ND

S	peci	ific	atio	n

Trim Colour Options	White		
Dimensions	600 (L) x 124 (W) x 60 (H) mm		
Weight	1180 g		
LED Power	16W		
LED Type	SMD		
Lumen Output	2350 lm		
Efficacy	Up to 103.94 lm/W		
CCT Technology	Tri-colour Switchable		
Colour Temperature	3000K, 4000K, 5700K		
Colour Rendering	CRI 85+		
Lifetime	50,000 hours (L70)		
Beam Angle	Very Wide		
System Power	18W Typical		
Input	220-240V AC 50/60 Hz		
Power Factor	>0.90		
Dimming	Non-dimmable		
Driver Type	Integral, Flicker Free		
Connection Type	Hardwired		
Ingress Protection	IP40		
Impact Resistance	IK08		
IEC Protection	Class II		
Warranty	3 Years		



















