

Skylyte PL0601

30 Watt 600mm Tricolour Square Panel

Square SMD LED panel manufactured with a powder coated aluminium frame with a low glare high output microprismatic diffuser which comes fitted as standard.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white) and 5700K (daylight). Supplied with a remote driver for easy maintenance.

Product	CCT	Trim Colour	Driver	Order Code
PL0601	Tricolour	White Trim	Non-dim	PL0601-TRI-W-ND
				Optional Association Available*

Optional Accessories Available*

Specifications

Trim Colour Options	White	
Dimensions	595 (L) x 595 (W) x 12 (H) mm	
Weight	2350 g	
LED Power	30W	
LED Type	SMD	
Lumen Output	3850 lm	
Efficacy	Up to 87 lm/W	
CCT Technology	Tri-colour Selectable	
Colour Temperature	3000K, 4000K, 5700K	
Colour Rendering	CRI 85+	
Lifetime	50,000 hours	
Beam Angle	Ultra Wide	
System Power	33W Typical	
Input	200-240V AC 50 Hz	
Power Factor	>0.95	
Dimming	Non-dimmable	
Driver Type	Remote, Flicker Free	
Connection Type	Hardwired	
Ingress Protection	IP20	
IEC Protection	Class II	
Warranty	3 Years	
Accessories*	Plaster Recessing Kit Surface	
	Mounting Kit Suspension Kit	



















