

Skylyte PL1201

30 Watt 1200mm Tri-colour Rectangular Panel

Rectangular SMD LED panel manufactured with a powder coated aluminium frame with a low glare high output microprismatic diffuser which comes fitted as standard.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white) and 5700K (daylight). Supplied with a remote driver for easy maintenance.

Product	CCT	Trim Colour	Driver	Order Code
PL1201	Tri-colour	White Trim	Non-dim	PL1201-TRI-W-ND
				Optional Association Available*

Optional Accessories Available*

Sp	ecifi	cati	ons

Trim Colour Options	White		
Dimensions	1195 (L) x 295 (W) x 12 (H) mm		
Weight	2550 g		
LED Power	30W		
LED Type	SMD		
Lumen Output	3850 lm		
Efficacy	Up to 87 lm/W		
CCT Technology	Tri-colour Switchable		
Colour Temperature	3000K, 4000K, 5700K		
Colour Rendering	CRI 85+		
Lifetime	50,000 hours		
Beam Angle	Ultra Wide		
System Power	33W Typical		
Input	200-240V AC 50 Hz		
Power Factor	>0.95		
Dimming	Non-dimmable		
Driver Type	Remote, Flicker Free		
Connection Type	Hardwired		
Ingress Protection	IP20		
IEC Protection	Class II		
Warranty	3 Years		
Accessories*	Plaster Recessing Kit Surface		
	Mounting Kit Suspension Kit		















