

Slot LSA20

20W Recessed Linear Wall Washer



LSA20 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
LSA20	2.7 (2700K)	(CRI 90+ Standard)	AS (Asymmetric)	W (White)	LT (Leading & Trailing Edge)
	3 (3000K)				
	4 (4000K)				

Order Code LSA204-AS-W-LT




To configure this linear light, please visit trendlighting.com.au/product/slot-LSA20

Physical Characteristics

Trim Colour	White		
Dimensions (LxWxH)	257 x 44 x 60 mm		
Cutout	Rectangular 250 x 37 mm		
Weight	320 g		

Dimensions (mm)

Cutout 250 x 37 mm



Product Features

- Recessed linear wall washer with fixed optics and defined cut off, enabling a precise wall wash effect
- Offers great vertical illumination and reduced lateral light spill, allowing for controlled environment
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with a remote driver and 240V flex and plug

Product Attributes











Technical Characteristics	Based on LSA204-AS-W-LT	
LED Power	20W	
LED Type	COB	

LED F LED T Lumen Output 2250 lm Luminous Flux 1050 lm Efficacy 42.68 lm/W 2700K | 3000K | 4000K Colour Temperature Colour Technology CRI 90+ Colour Deviation SDCM ≤ 3 50,000 hours (L70) Lifetime Beam Angle Asymmetric

System Power	24.6W Typical
Driver Model	Trend 150013-700 (L&T)
Input	180-265V AC 50/60 Hz
Output	11-18V DC 700mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge

General Characteristics

Category	Linears & Battens, Wall Washers		
Family	Slot		
Surface	Ceiling		
Mounting	Recessed		
Insulation Contact	Non-IC		
Ingress Protection	IP43		





20W Recessed Linear Wall Washer



Scan to explore LSA20 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
LSA20	2.7 (2700K) 3 (3000K) 4 (4000K)	(CRI 90+ Standard)	AS (Asymmetric)	W (White)	LT (Leading & Trailing Edge)

Order Code LSA204-AS-W-LT

To configure this linear light, please visit

trendlighting.com.au/product/slot-LSA20

Trim Colour



W White Trim