

# **Surface XSI15**

15W Surface Mounted Square Downlight



Scan to explore XSI15 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
XSI15	2.7 (2700K)	(CRI 90+ Standard)	WB (Wide)	W (White)	HL (Honeycomb Lens)	ND (Non-dimmable)
	3 (3000K)	V (CRI 93+ VIVID)		B (Black)		DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)				110V (1-10V)
	4 (4000K)					

Order Code XSI154-WB-B-ND \* Optional accessories




To configure this downlight, please visit <a href="mailto:trendlighting.com.au/product/surface-XSI15">trendlighting.com.au/product/surface-XSI15</a>

## **Physical Characteristics**

Trim Colour	White   Black
Dimensions (LxWxH)	90 x 90 x 157 mm
Weight	1300 g

# Dimensions (mm)



#### **Product Features**

- Surface mounted square LED downlight with high efficiency collimator lens; available with optional honeycomb lens
- Die cast aluminium body with integrated heatsink design for optimal thermal management
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with an integral driver

#### **Product Attributes**









Technical Characteristics	Based on XSI154-WB-B-ND			
LED Power	15W			
LED Type	COB			
Lumen Output	2004 lm			
Luminous Flux	1460 lm			
Efficacy	80.22 lm/W			
Colour Temperature	2700K   3000K   3500K   <b>4000K</b>			
Colour Technology	CRI 90+   CRI 93+ VIVID   CRI 97+			
Colour Deviation	SDCM ≤ 2			
Lifetime	50,000 hours (L80)			
Beam Angle	Wide			
System Power	18.2W Typical			
Driver Model	Trend 150079-500 (Non-dim)			
Input	220-240V AC 50/60 Hz			
Output	25-42V DC 500mA			
Power Factor	>0.90			
Protection	OVP, OTP, OCP, SCP, OPP			
Dimming	Non-dimmable   DALI   1-10V			

## **General Characteristics**

Category	Downlights		
Family	Surface		
Surface	Ceiling		
Mounting	Surface Mounted		
Ingress Protection	IP20		



# **Surface XSI15**

15W Surface Mounted Square Downlight



Scan to explore XSI15 online

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Accessories *	Driver
XSI15	2.7 (2700K) 3 (3000K)	(CRI 90+ Standard) V (CRI 93+ VIVID)	WB (Wide)	W (White) B (Black)	HL (Honeycomb Lens)	ND (Non-dimmable) DALI (DALI)
	3.5 (3500K) 4 (4000K)	R (CRI 97+ Standard)				110V (1-10V)

Order Code XSI154-WB-B-ND \* Optional accessories

To configure this downlight, please visit

trendlighting.com.au/product/surface-XSI15

## **Trim Colour**





White Trim

Black Trim

# Accessories \*



HL Honeycomb Lens