




SURFACE LED XSR2510-IP65

10 Watts / 1390 Lumens / 90+ CRI



IP65 Rated 10 watt Surface Mounted LED downlight available in 2700K, 3000K, 4000K and 5000K colour temperature options in 90+ CRI or 2700K,3000K and 4000K VIVID options. Supplied with integral LED driver.



System Power 14.9 W
LED Power 10 W
IP Rating IP65

Weight 1490g

	2700K	3000K	4000K	5000K	VIVID	2700K	3000K	4000K
COB Lumen Output	1300 lm	1335 lm	1390 lm	1410 lm	VIVID	1080 lm	1120 lm	1150 lm
Total Luminous Flux	1185 lm	1220 lm	1275 lm	1295 lm	VIVID	965 lm	1005 lm	1035 lm

Efficacy	85.57 lm/W 4000K Wide Beam	Lifetime	50,000hrs (L80)
Dimming	Optional: Dali		
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit
		Power Factor	> 0.95



Product	CCT	Light Source	Beam Angle	Trim Colour	Insert Colour	Driver
XSR2510-IP65	2700K 2.7	90+ CRI	Wide Beam WB	White W	Black Insert BT	none
	3000K 3	VIVID* V	Medium Beam MB	Black B	White Insert* WT	DALI* DALI
	4000K 4		Narrow Beam NB	Silver S	Silver Insert* ST	
	5000K 5				Gold Insert* GT	
XSR2510-IP65	3		WB	W	BT	

XSR2510-IP65-3-WB-W-BT

* Optional



TREND
LIGHT BY SOLID STATE

Level 3, 290-292 Coward Street, Mascot, NSW, 2020
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au