

# Wireguard ZBW

20 Watts / 2500 Lumens / 85+ CRI

40 Watts / 5500 Lumens / 85+ CRI

Surface Mounted linear LED wire guard batten manufactured using Japanese based die's featuring 150lm/w technology. Powdercoated body with acrylic diffuser for smooth uniform light distribution and steel wire guard for increased impact resistance. Internally mounted 4mm Terminal block included for ease of installation.

Available as a 4 hour Maintained or Non-Maintained battery backup emergency system.

Input Voltage 240V

Lamp Type LED

IP Rating IP20

Weight 1300g

ZBW224

System Power 20.0W

LED Power 18W

ZBW444

System Power 44.9W

LED Power 40W


## ZBW Specifications

	ZBWP224	ZBW444
COB Lumen Output	2500 lm	5500 lm
Total Luminous Flux	2194 lm	4906 lm
Efficacy	110 lm/W	109 lm/W
Lifetime	50,000hrs (L70)	
Power Factor	> 0.96	
Input Voltage	220V - 240V AC 50/60 Hz	
Protection	Thermal and Short Circuit	
Dimming	DALI* 1-10v* Available on request	
Emergency Systems	Optional 4 hour Battery Backup available	

## ZBW Dimensions



## ZBW Trim Colours



White

## ZBW Order Code



**TREND**  
LIGHT BY SOLID STATE

Level 3, 290-292 Coward Street, Mascot, NSW, 2020  
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au