



Scan to explore  
XF2499 online

# Flexiled XF2499

20W/m 24V DC Flexible Strip

Product Code	Colour Temperature	Colour Technology	Length *	Driver
XF2499	2.7 (2700K)	(CRI 90+ Standard)	1000 (1000 mm)	NA (No Driver)
	3 (3000K)		XXXX (Custom)	ND (Non-dimmable)
	4 (4000K)			DALI (DALI)
	5 (5000K)			110V (1-10V)

Order Code **XF24994-1000-NA**

\* Custom lengths available



## Product Features

- Flexible LED strip with a close pitch of 99 LEDs per metre for reduced spotting effects
- Available in reels up to 6 metres with cuttable intervals of 60 mm
- Supplied with 3M adhesive backing for quick and easy installation
- CRI 90+ available in 2700K, 3000K, 4000K and 5000K CCT options
- Can be paired with a range of extrusion profiles to suit a variety of lighting applications

To configure this LED strip, please visit  
[trendlighting.com.au/product/flexiled-XF2499](http://trendlighting.com.au/product/flexiled-XF2499)

## Product Attributes




## Physical Characteristics

Dimensions (LxWxH)	1000 x 12 x 2 mm
Max. Reel Length	6000 mm *

\* Custom lengths available

## Dimensions (mm)




## Technical Characteristics

Based on XF24994-1000-NA

Input Voltage	24V DC
LED Power	20W per metre
LED Type	SMD
Lumen Output	2300 lm
Colour Temperature	2700K   3000K   4000K   5000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours
LED Pitch	99 LEDs per metre
LED Cutting Increment	60 mm (6 LEDs)
Backing	Adhesive Backing 3M 300LSE
Copper Content	2oz PCB

## General Characteristics

Category	Strips & Extrusions
Family	Flexiled
Surface	Ceiling   Floor   Wall
Mounting	Surface Mounted
Ingress Protection	IP10



Scan to explore  
XF2499 online

# Flexiled XF2499

20W/m 24V DC Flexible Strip

Product Code	Colour Temperature	Colour Technology	Length *	Driver
<b>XF2499</b>	2.7 (2700K)	(CRI 90+ Standard)	1000 (1000 mm) XXXX (Custom)	NA (No Driver)
	3 (3000K)			ND (Non-dimmable)
	4 (4000K)			DALI (DALI)
	5 (5000K)			110V (1-10V)

Order Code **XF24994-1000-NA**

\* Custom lengths available

To configure this LED strip, please visit  
[trendlighting.com.au/product/flexiled-XF2499](http://trendlighting.com.au/product/flexiled-XF2499)

## Applicable Extrusions for Flexiled XF2499

1/2



**Extrusion EX1**  
Surface Mounted Trimless  
Angled Corner Extrusion

Max. Length 3000 mm  
Trim Colour Silver  
Opal Lens | Clear Lens



**Extrusion EX2**  
Surface Mounted  
Extrusion

Max. Length 3000 mm  
Trim Colour Black | Silver  
Opal Lens | Clear Lens



**Extrusion EX4**  
Recessed Extrusion

Max. Length 3000 mm  
Trim Colour Black | Silver  
Opal Lens | Clear Lens



**Extrusion EX5**  
Surface Mounted Angled  
Corner Extrusion

Max. Length 3000 mm  
Trim Colour Black | Silver  
Opal Lens | Clear Lens









**Extrusion EX6**  
Surface Mounted  
Extrusion

Max. Length 3000 mm  
Trim Colour Black | White  
Opal Lens



**Extrusion EX7**  
Recessed Extrusion

Max. Length 3000 mm  
Trim Colour Black | Silver  
Opal Lens | Clear Lens



**Extrusion EX8**  
Surface Mounted Angled  
Corner Extrusion

Max. Length 3000 mm  
Trim Colour Black | White  
Opal Lens | Clear Lens



**Extrusion EXM**  
Surface Mounted Sleek  
Magnetic Extrusion

Max. Length 3000 mm  
Trim Colour Black | Silver  
Opal Lens



**Extrusion EX12R**  
Semi-Round Extrusion

Max. Length 3000 mm  
Trim Colour Black | White  
Opal Lens








**Extrusion EX241**  
Recessed Extrusion with  
Narrow Profile

Max. Length 3000 mm  
Trim Colour Black | White  
Opal Lens



**Extrusion EX245**  
Recessed Extrusion with  
Wide Profile

Max. Length 3000 mm  
Trim Colour Black | White  
Opal Lens





Scan to explore  
XF2499 online

# Flexiled XF2499

20W/m 24V DC Flexible Strip

Product Code	Colour Temperature	Colour Technology	Length *	Driver
XF2499	2.7 (2700K)	(CRI 90+ Standard)	1000 (1000 mm)	NA (No Driver)
	3 (3000K)		XXXX (Custom)	ND (Non-dimmable)
	4 (4000K)			DALI (DALI)
	5 (5000K)			110V (1-10V)

Order Code **XF24994-1000-NA**

\* Custom lengths available

To configure this LED strip, please visit  
[trendlighting.com.au/product/flexiled-XF2499](http://trendlighting.com.au/product/flexiled-XF2499)

## Applicable Extrusions for Flexiled XF2499

2/2



**Extrusion ZDA**  
Surface Mounted Streamline Extrusion

Max. Length 3600 mm  
Trim Colour Black | White  
Opal Lens



**Extrusion ZDA-D**  
Suspended Uni-directional Streamline Extrusion

Max. Length 3600 mm  
Trim Colour Black | White  
Opal Lens







**Extrusion ZDA-DI**  
Suspended Bi-directional Streamline Extrusion

Max. Length 3600 mm  
Trim Colour Black | White  
Opal Lens



**Extrusion ZTL**  
Surface Mounted Wide Extrusion

Max. Length 4800 mm  
Trim Colour Black | White  
Opal Lens



**Extrusion ZTL-D**  
Suspended Wide Extrusion

Max. Length 4800 mm  
Trim Colour Black | White  
Opal Lens

