

Wall WRD14

2 x 5.8W IP65 Rated Classic Bi-directional Wall Light



Scan to explore WRD14 online

Product Code	Colour Temp	perature Colour Technolog	y Beam Angle	Trim Colour	Driver
WRD14	3 (3000K)	(CRI 90+ Standard)	WB (Wide)	W (White)	ND (Non-dimmable)
	4 (4000K)			B (Black)	

Order Code WRD144-WB-B-ND




To configure this wall light, please visit trendlighting.com.au/product/wall-WRD14

Physical Characteristics

Trim Colour	White Black
Dimensions	Ø60 x 170 (H) mm
Weight	680 g

Dimensions (mm)



Product Features

- Surface mounted IP65 rated sleek wall light in a bi-directional light configuration
- Manufactured from an aluminium body and powder coat finish
- Sealed safety glass lens for ingress protection
- Characterised by its black print insert, allowing for seamless integration with contemporary architecture
- CRI 90+ available in 3000K and 4000K CCT options
- Supplied with integral driver

Product Attributes







Technical Characteristics



8W	

LED Power	2 x 5.8W
LED Type	COB
Lumen Output	1499 lm
Luminous Flux	881 lm
Efficacy	73.42 lm/W
Colour Temperature	3000K 4000K
Colour Technology	CRI 90+
Colour Deviation	SDCM ≤ 3
Lifetime	50,000 hours (L70)
Beam Angle	Wide

System Power	12W Typical
Driver Model	Trend DR-WRD14 (Non-dim)
Input	100-240V AC 50/60 Hz
Power Factor	>0.95
Dimming	Non-dimmable

General Characteristics

Category	Exterior
Family	Wall
Surface	Wall
Mounting	Surface Mounted
Ingress Protection	IP65



Wall WRD14



Scan to explore WRD14 online

2 x 5.8W IP65 Rated Classic Bi-directional Wall Light

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Driver
WRD14	3 (3000K) 4 (4000K)	(CRI 90+ Standard)	WB (Wide)	W (White) B (Black)	ND (Non-dimmable)

Order Code WRD144-WB-B-ND

To configure this wall light, please visit

trendlighting.com.au/product/wall-WRD14

Trim Colour





W White Trim B Black Trim