

## Bayled TPU90150

IP65 & IK10 Rated Tri-select Highbay

Highbay manufactured with a robust integrated aluminium heatsink and precision-engineered cooling fins for optimal heat dissipation, ensuring longevity and efficiency. Equipped with a heavy-duty loop and hook for secure mounting, it also offers additional mounting options upon request, providing versatility to suit various installation needs.


Featuring tri-select technology, allowing users to switch between three wattage options (90W, 120W, 150W), three beam angles (60°, 90°, 120°) and three CCT options (3000K, 4000K, 5000K) offering the ultimate versatility for high bay applications. Supplied with an integral flicker free IP65 rated driver.




Product	ССТ	Trim Colour	Driver	Order Codes
TPU90150	Tri-colour	Black Trim	Non-dim	TPU90150-TRI-B-ND

Sp	ecific	catio	ns

Trim Colour Options	Black
Dimensions	Ø280 x 142 (H) mm
Weight	1653 g
LED Power	90W, 120W, 150W
LED Type	SMD
Lumen Output	12500 lm, 17400 lm, 21000 lm
Efficacy	139 lm/W, 145 lm/W, 140 lm/W
CCT Technology	Switchable CCT
Colour Temperature	3000K, 4000K, 5000K
Colour Rendering	CRI 80+
Lifetime	50,000 hours
Beam Angle	Adjustable 60°, 90°, 120°
System Power	93.4W, 122.3W, 151.8W Typical
Input	220-240V AC 50/60 Hz
Power Factor	>0.90
Dimming	Non-dimmable
Driver Type	Integral, Flicker Free
Connection Type	2 m, Flex and Plug
Ingress Protection	IP65
Impact Resistence	IK10
Warranty	3 Years
	·



Diameter 280 mm



Diameter 280 mm

















