

### Flexiled XF24480

9W/m 24V DC Flexible COB Strip



Scan to explore XF24480 online

Product Code	Colour Temperature	Colour Technology	Length *	Driver
XF24480	3 (3000K)	(CRI 90+ Standard)	1000 (1000 mm)	NA (No Driver)
	4 (4000K)		XXXX (Custom)	ND (Non-dimmable)
				DALI (DALI)
				110V (1-10V)

Order Code XF244804-1000-NA

#### **Product Features**

- Flexible LED strip with a close pitch of 480 LEDs per metre and shared linear phosphor for a continuous and even light emission
- Available in reels up to 5 metres with a cutting interval of 50 mm
- Supplied with adhesive backing for quick and easy installation
- CRI 90+ available in 3000K and 4000K CCT options
- Can be paired with a variety of extrusion profiles to suit any interior scheme

trendlighting.com.au/product/flexiled-XF24480

### Physical Characteristics

To configure this LED strip, please visit

Dimensions (LxWxH)	1000 x 8 x 2 mm	
Max. Reel Length	5000 mm*	

<sup>\*</sup> Custom lengths available

#### Dimensions (mm)



#### **Product Attributes**









#### **Technical Characteristics** Based on XF244804-1000-NA 24V DC Input Voltage LED Power 9W per metre LED Type СОВ Lumen Output 1000 lm 3000K | 4000K Colour Temperature Colour Technology CRI 90+ Colour Deviation SDCM ≤ 3 Lifetime 50,000 hours LED Pitch 480 LEDs per metre LED Cutting Increment 50 mm Backing Adhesive Backing

2oz PCB

#### **General Characteristics**

Copper Content

Strips & Extrusions	
Flexiled	
Ceiling   Floor   Wall	
Surface Mounted	
IP20	

<sup>\*</sup> Custom lengths available



### Flexiled XF24480

9W/m 24V DC Flexible COB Strip



XF24480 online

Product Code	Colour Temperature	Colour Technology	Length *	Driver
XF24480	3 (3000K)	(CRI 90+ Standard)	1000 (1000 mm)	NA (No Driver)
	4 (4000K)		XXXX (Custom)	ND (Non-dimmable)
				DALI (DALI)
				110V (1-10V)

Order Code XF244804-1000-NA

\* Custom lengths available

To configure this LED strip, please visit

trendlighting.com.au/product/flexiled-XF24480

#### **Applicable Extrusions for Flexiled XF24480**

1/2



Extrusion EX1 Surface Mounted Trimless Angled Corner Extrusion

Max. Length 3000 mm Trim Colour Silver Opal Lens | Clear Lens





**Extrusion EX2** Surface Mounted Extrusion

Max. Length 3000 mm Trim Colour Black | Silver Opal Lens | Clear Lens





Extrusion EX3 Recessed Extrusion with

Max. Length 3000 mm Trim Colour Black | White | Silver Opal Lens





Extrusion EX4

Max. Length 3000 mm Trim Colour Black | Silver Opal Lens | Clear Lens






Extrusion EX5 Surface Mounted Angled Corner Extrusion

Max. Length 3000 mm Trim Colour Black | Silver Opal Lens | Clear Lens






Extrusion EX6





Extrusion EX7 Recessed Extrusion


Max. Length 3000 mm Trim Colour Black | Silver Opal Lens | Clear Lens





**Extrusion EX8** Surface Mounted Angled Corner Extrusion

Max. Length 3000 mm Trim Colour Black | White Opal Lens | Clear Lens





**Extrusion EXM** Surface Mounted Sleek Magnetic Extrusion

Max. Length 3000 mm Trim Colour Black | Silver Opal Lens






Extrusion EX12R Semi-Round Extrusion

Max. Length 3000 mm Trim Colour Black | White Opal Lens



Extrusion EX241 Recessed Extrusion with Narrow Profile

Max. Length 3000 mm Trim Colour Black | White Opal Lens





## Flexiled XF24480





Scan to explore XF24480 online

Product Code	Colour Temperature	Colour Technology	Length *	Driver
XF24480	3 (3000K)	(CRI 90+ Standard)	1000 (1000 mm)	NA (No Driver)
	4 (4000K)		XXXX (Custom)	ND (Non-dimmable)
				DALI (DALI)
				110V (1-10V)

Order Code XF244804-1000-NA

\* Custom lengths available

To configure this LED strip, please visit

trendlighting.com.au/product/flexiled-XF24480

### **Applicable Extrusions for Flexiled XF24480**

2/2



# **Extrusion EX245**Recessed Extrusion with Wide Profile

Max. Length 3000 mm Trim Colour Black | White Opal Lens

