



Scan to explore
XDM30 online

Midiled XDM30

30W Adjustable Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XDM30	2.7 (2700K)	(CRI 90+ Standard)	MB (Medium)	W (White)	WI (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	WB (Wide)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)		S (Silver)	SI (Silver)	
	4 (4000K)				GI (Gold)	

Order Code **XDM304-WB-W-WI-LT**



To configure this downlight, please visit
trendlighting.com.au/product/midiled-XDM30

Product Features

- Recessed adjustable LED downlight, distinctively characterised by its configurable inserts that can suit any interior scheme
- Manufactured with an aluminium body and powder coat finish
- Large pin fin heatsink for optimal thermal management
- Also available in other configurations ([XDM10](#), [XDM15](#) and [XDM25](#))
- CRI 90+ available in 2700K, 3000K, 3500K and 4000K CCT options; CRI 93+ VIVID and CRI 97+ available in 2700K, 3000K and 4000K CCT options
- Supplied with a remote driver


Product Attributes



Physical Characteristics

Trim Colour	White Black Silver
Insert Colour	White Black Silver Gold
Tilt Angle	25°
Dimensions	Ø150 x 125 (H) mm
Spring Height	35 mm
Cutout	Circular 120 mm
Weight	515 g

Dimensions (mm)



 Cutout Ø120 mm

Technical Characteristics

Based on XDM304-WB-W-WI-LT

LED Power	30W
LED Type	COB
Lumen Output	4746 lm
Luminous Flux	2801 lm
Efficacy	88.64 lm/W
Colour Temperature	2700K 3000K 3500K 4000K
Colour Technology	CRI 90+ CRI 93+ VIVID CRI 97+
Colour Deviation	SDCM ≤ 2
Lifetime	50,000 hours (L80)
Beam Angle	Medium Wide

System Power	31.6W Typical
Driver Model	Trend 150045-850 (L&T)
Input	220-240V AC 50/60 Hz
Output	34-40V DC 850mA
Power Factor	>0.90
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge DALI

General Characteristics

Category	Downlights
Family	Midiled
Surface	Ceiling
Mounting	Recessed
Insulation Contact	Non-IC
Ingress Protection	IP20



Scan to explore
XDM30 online

Midiled XDM30

30W Adjustable Recessed Downlight

Product Code	Colour Temperature	Colour Technology	Beam Angle	Trim Colour	Insert Colour	Driver
XDM30	2.7 (2700K)	(CRI 90+ Standard)	MB (Medium)	W (White)	WI (White)	LT (Leading & Trailing Edge)
	3 (3000K)	V (CRI 93+ VIVID)	WB (Wide)	B (Black)	BI (Black)	DALI (DALI)
	3.5 (3500K)	R (CRI 97+ Standard)		S (Silver)	SI (Silver)	
	4 (4000K)				GI (Gold)	

Order Code **XDM304-WB-W-WI-LT**

To configure this downlight, please visit
trendlighting.com.au/product/midiled-XDM30

Trim Colour



W
White Trim



B
Black Trim



S
Silver Trim

Insert Colour



WI
White Insert



BI
Black Insert



SI
Silver Insert



GI
Gold Insert