

Nero WP1201

40 Watt IP65 & IK08 Rated 1200mm Tri-colour Weatherproof Batten

Surface mounted SMD LED weatherproof batten with IK08 impact protection. Manufactured from ABS plastic with an impact resistant polycarbonate diffuser for soft uniform light distribution. Integrated latch design allows access to the conveniently mounted terminal block for easy installation.

Featuring colour switchable technology that enables users to switch between 3 colour temperature options - 3000K (warm white), 4000K (cool white) and 5700K (daylight). Supplied with an integral non-dimmable driver. Optional motion sensor available.








Product	CCT	Trim Colour	Driver	Sensor*	Order Codes
WP1201	Tri-colour	White Trim	Non-dim		WP1201-TRI-W-ND
					WP1201-TRI-W-ND-MMS*

Optional Sensor Available*

Specifications

Trim Colour Options	White		
Dimensions	1215 (L) x 116 (W) x 74 (H) mm		
Weight	1950 g		
LED Power	38W		
LED Type	SMD		
Lumen Output	4200 lm		
Efficacy	Up to 105 lm/W		
CCT Technology	Tri-colour Switchable		
Colour Temperature	3000K, 4000K, 5700K		
Colour Rendering	CRI 85+		
Lifetime	50,000 hours		
Beam Angle	Very Wide		
System Power	40W Typical		
Input	200-240V AC 50 Hz		
Power Factor	>0.95		
Dimming	Non-dimmable		
Driver Type	Integral, Flicker Free		
Connection Type	Hardwired		
Ingress Protection	IP65		
Impact Protection	IK08		
Sensor Type*	Microwave Motion Sensor		
IEC Protection	Class II		
Warranty	3 Years		



Width 116 mm

Length 1215 mm

CCT CRI









