

# **Platinum P12R**

#### 12W IP65 Rated Recessed Premium Downlight



. <u>P12R</u> online

\* Optional accessories

Product Code	Tri	m Colour	Colour Temperat	ure Colour Technology	Beam Angle		Accessories *	Driver		
P12R	W B	<b>(White)</b> (Black)	927 (2700K) 930 (3000K) 935 (3500K) 940 (4000K)	(CRI 94+ Standard) S (CRI 98+ Optisolis)	20D 38D	(Narrow) (Medium)	SDR (Specular Dark Reflector)	<b>LT</b> DALI	(Leading & Trailing Edge) (DALI)	

Order Code P12RW-940-38D-LT




To configure this downlight, please visit trendlighting.com.au/product/platinum-P12R

#### **Physical Characteristics**

Trim Colour	White   Black				
Dimensions	Ø92 x 120 (H) mm				
Spring Height	50 mm				
Cutout	Circular 78 mm				
Weight	230 g				

#### Dimensions (mm)



Cutout Ø78 mm

### **Product Features**

- Deep recessed IP65 rated premium LED downlight known for its thin trim profile and low glare design
- Manufactured with an aluminium body and powder coat finish
- Injection moulded twice vacuum metalised reflector for high reflectivity and uniform beam distribution
- Can be specified with specular dark reflector
- CRI 94+ and CRI 98+ Optisolis available in 2700K, 3000K, 3500K and 4000K CCT options
- Supplied with a remote driver

#### **Product Attributes**



Technical Characteristics	Based on P12RW-940-38D-L
LED Power	10W
LED Type	COB
Lumen Output	1350 lm
Luminous Flux	1072 lm
Efficacy	90.08 lm/W
Colour Temperature	2700K   3000K   3500K   <b>4000K</b>
Colour Technology	CRI 94+   CRI 98+ Optisolis
Colour Deviation	$SDCM \le 2$
Lifetime	60,000 hours (L80 B10)
Beam Angle	Narrow   Medium
System Power	11.9W Typical
Driver Model	Trend 150218-300 (L&T) Black
Input	180-265V AC 50/60 Hz
Output	30-42V DC 300mA
Power Factor	>0.93
Protection	OVP, OTP, OCP, SCP, OPP
Dimming	Leading & Trailing Edge   DALI

## **General Characteristics**

Category	Downlights
Family	Platinum
Surface	Ceiling
Mounting	Recessed
Insulation Contact	CA90
Ingress Protection	IP65



# **Platinum P12R**

12W IP65 Rated Recessed Premium Downlight



P12R online

Product Code	Tri	m Colour	Colour Temperature		Colour Technology	Beam Angle		Accessories *		Driver	
P12R	W B	<b>(White)</b> (Black)	927 (2700K) 930 (3000K) 935 (3500K) <b>940 (4000K)</b>		(CRI 94+ Standard) S (CRI 98+ Optisolis)	20D 38D	(Narrow) (Medium)	SDR (Specular [	Dark Reflector)	<b>LT</b> DALI	(Leading & Trailing Edge) (DALI)

Order Code P12RW-940-38D-LT

\* Optional accessories

To configure this downlight, please visit

trendlighting.com.au/product/platinum-P12R

### Trim Colour






W White Trim

B Black Trim

# Accessories \*



SDR Specular Dark Reflector